

Tank Gauge O.L.E. C2020 +/- 1% Accuracy

HYTEK
Fuel Transfer Solutions



ADBLUE®

DIESEL

B100

ANTIFREEZE

H₂O

HVO



Tank Gauge

O.L.E. C2020 +/- 1% Accuracy

Depending on the amount of fuel you use, a more accurate tank gauge can be very cost effective. In fact it normally pays for itself over a short period of time, worth doing your sums!

- Suitable for any shape tank.
- Accuracy +/- 1% of tank capacity.
- Suitable with diesel, biodiesel up to B100, AdBlue® & antifreeze.
- Electronic display with backlight (turns off after 1 hour).
- Gives continuous readout in litres (screen also shows a % bar).
- Includes 4-20mA outputs.
- Can connect to a BMS (building management system).
- One gauge required per tank.
- Weatherproof to IP55 suitable for outside mounting.
- Voltage 110V/230V.
- Suits tanks 0.3 - 5m high. (AdBlue® version 0.6 - 2.5m).
- Probe must be suspended 50mm from tank bottom.

Stk Code	Description
C2020-A-C23	Tank gauge kit 0.3m-3m with high & low level alarms (110dB)
C2020-A-C25	Tank gauge kit 3 - 5m with high & low level alarms (110dB)
C2020-C27	Tank gauge kit 5-10m with high & low level alarms (110dB)
B8	Bund probe only, for use with alarm kit option
T4020-B2	Water bottom sensor (min 15mm of water required) for use with alarm kit option
T4020-OJ	Probe/tank adaptor fits a 30mm hole

Options

- C2020-A-C23,25 with high/low level alarm, can also have a bund probe or water bottom sensor option.
- Choose bund probe (B8) &/or water bottom sensor (T4020-B2).
- Water bottom sensor requires 15mm of water to activate.

Supplied by

